

---

# STORMWATER MANAGEMENT BENEFITS OF TREES

## FINAL REPORT

Stone Project ID 12-161

March 11, 2014

**Prepared for:**

Urban and Community Forestry, Vermont Dept. of Forests,  
Parks & Rec.

Danielle Fitzko

1 National Life Drive, Davis 2

Montpelier, VT 05620-3801

Tel. / 802.598.9992

E-Mail / [Danielle.fitzko@state.vt.us](mailto:Danielle.fitzko@state.vt.us)

**Prepared by:**

Stone Environmental, Inc.

Julie Moore, Amy Macrellis, Kate Bailey

535 Stone Cutters Way

Montpelier, VT 05602

Tel. / 802.229.1881

E-Mail / [jmoore@stone-env.com](mailto:jmoore@stone-env.com)

## **ACKNOWLEDGEMENTS**

This project was performed by Stone Environmental, Inc. for the Vermont Department of Forests, Parks, and Recreation with funding provided by the U.S. Forest Service Northeastern Area State and Private Forestry Competitive Allocation. We are grateful for constructive technical review comments provided by Kestrel Design Group of Minneapolis, Minnesota.

---

## TABLE OF CONTENTS

ACKNOWLEDGEMENTS .....	ii
1. INTRODUCTION.....	4
2. TREE PROCESSES THAT AFFECT STORMWATER RUNOFF .....	4
2.1. Interception.....	5
2.2. Transpiration .....	5
2.3. Infiltration.....	7
2.4. Pollutant removal.....	8
3. MAXIMIZING STORMWATER –RELATED BENEFITS AT THE TREE OR SITE SCALE .....	9
3.1. Soil Restoration and Tree Planting.....	10
3.2. Engineered Systems for Trees in Urban Settings.....	10
3.2.1. Suspended pavement and structural cells .....	11
3.2.2. Structural soil .....	11
3.2.3. Stormwater tree pits.....	11
3.2.4. Forested bioretention and bioinfiltration .....	12
3.3. Tree Selection, Siting, and Planting .....	12
4. REFERENCES.....	14

## LIST OF FIGURES

Figure 1. Diagram of water movement through trees. Source: US EPA 2013.....	4
Figure 2: Monthly average precipitation and evaporation at the Burlington International Airport, 1975-2004 (NRCC and NCDC, 2014) .....	6
Figure 3. Comparison of uncompacted soil volume to projected mature tree size (trunk and canopy diameter), with estimates of stormwater storage per tree (Deep Root Partners 2011).....	9
Figure 4. A structural cell system under construction on Cherry Street in Burlington, VT. ....	11

# 1. INTRODUCTION

Trees provide us with a host of wildlife and habitat benefits, energy savings, social and health benefits, and economic benefits. Trees also act as natural reservoirs by intercepting and storing rainfall, which can reduce runoff volume and mitigate its effects (Midwest Urban Tree Canopy Project 2011). The benefits of trees as stormwater management practices, especially in urban and suburban settings, have recently been more widely recognized. Here, we summarize recent work describing and quantifying the stormwater management benefits of trees, especially at the individual tree and property/site scales.

# 2. TREE PROCESSES THAT AFFECT STORMWATER RUNOFF

Three primary processes—interception, transpiration, and infiltration—can reduce the amount of rain falling on trees that becomes stormwater runoff.

- **Interception** occurs first, when precipitation collects on leaves, branches, and trunks and evaporates or is absorbed. This process reduces the amount of water reaching the ground, delaying the onset and reducing the volume of peak flows (U.S. EPA 2013).
- **Transpiration** is the transfer of water from the soil through the tree and its eventual release in a gaseous form through microscopic pores in the leaves and stems (Herrera Environmental Consultants 2008).
- **Infiltration** is the movement of surface water through the soil. Tree roots, combined with the organic material that typically builds on the soil at the base of trees, promote the infiltration of runoff through shallow subsurface zones, reducing both the rate and volume of stormwater runoff (U.S. EPA 2013).

**Pollutant removal** is another important function performed both by trees and by the soils they grow in. Along with water, trees take up nutrients and trace amounts of chemicals, including metals, organic compounds, fuels, and solvents from the soil (US EPA 2013). Inside the tree, pollutants may be transformed into less harmful substances, used as nutrients, or stored in roots, stems, and leaves.




Figure 1. Diagram of water movement through trees. Source: US EPA 2013

### 2.1. Interception

There is a reasonably robust body of literature regarding the interception of precipitation by trees. Research indicates that conifers generally intercept more water annually than deciduous trees, which can be explained by the greater foliage surface area of conifers and the presence of foliage on conifers during winter months (Herrera Environmental Consultants 2008).

Interception is dependent on the tree species and rainfall characteristics. Measured rainfall interception for individual trees ranges from 8% to 68% of a rainfall event (Capiella et al. 2006, Herrera Environmental Consultants 2008), and can sometimes even higher, e.g. 79.5% measured during a 20.3 mm (0.8 inch) summer storm for a large, deciduous *Platanus acerifolia* tree (Xiao and McPherson 2002). Canopy interception measured for conifer stands ranges from 15% to 51% of annual precipitation, and interception in hardwood stands ranges from 8% to 20% (Xiao et al. 2000, Herrera Environmental Consultants 2008).

### 2.2. Transpiration

Evapotranspiration (ET) is the sum of water evaporated from soil and plant surfaces and the water lost as a result of transpiration, a process in which trees absorb water through their roots and transfer it up to the leaves, where it evaporates into the environment through leaf pore transpiration (Shanstrom 2011a). Transpiration from plants and trees continues to reduce water volumes stored in the soil long after a rainfall event ends.

Only a few recent studies have attempted to quantify the rate of transpiration associated with different types of trees (Herrera Environmental Consultants 2008). These studies found that conifers transpired 10-12% of precipitation, while deciduous trees during leaf-on transpired up to 25% of precipitation. Evergreens have lower transpiration rates because they are more efficient than deciduous trees at retaining moisture, due to the structure of their leaves (Metro, 2002). Those percentages can sometimes amount to a substantial portion of smaller storms falling on individual trees. A mature tree can, on average, transpire 100 gallons of water per day (Akbari et al. 1992; Metro 2002), while an acre of mature forest can take up at least 1,800 gallons of water every day (Envirocast, 2003). Transpiration rates (along with rooting depth and trunk growth) can, however, be restricted under slow soil drainage rates (Bartens et al. 2009).

In many parts of the US, potential evapotranspiration is much greater than the amount of precipitation during the growing season, so directing runoff from adjacent impervious surfaces to trees, or harvesting stormwater and using it to irrigate trees, can increase the volume of rain trees abstract from the stormwater system through ET. For example, a study by Grimmond and Oke (1999) which compared the ratio of ET to precipitation (ET:P) in seven North American cities with very different climates found that in many cities, ET exceeds precipitation and is sustained by irrigation from a municipal water supply. ET:P ratios ranged from 0.7 to 3.7 for sites with precipitation. A ratio of 3.7 means that ET was almost 4 times as high as the amount of rain that fell.

Even given Vermont's relatively cold climate and short growing season, the portion of precipitation lost to ET is substantial. For example, based on 1975-2004 climate records from the Burlington airport, mean annual precipitation was 35.5 inches, while mean annual potential ET was 21.9 inches (NRCC and NCDC, 2014). Thus, on an average annual basis, approximately 62% of precipitation is being evapotranspired. During the growing season, for this same time period, atmospheric evaporative demand exceeds precipitation (see Figure 2). This "deficit" indicates that for some portions of Vermont's growing season, if more water was available than just precipitation, ET could exceed precipitation.




Figure 2: Monthly average precipitation and evaporation at the Burlington International Airport, 1975-2004 (NRCC and NCDC, 2014)

Evapotranspiration tends to be highest when soil moisture is highest, and decreases as soil moisture decreases. An investigation of daily transpiration response to soil drying in five woody species (Sinclair et al. 2005) found that transpiration was unaffected by soil drying until the initial estimated transpirable soil water fraction had decreased to between 0.23 and 0.32 of that at field capacity. Beyond this point, transpiration rate declined linearly with available soil water fraction until reaching one fifth the rate observed in well watered plants. With further soil drying, the relative transpiration rates remained between 10 and 20% of that observed in well watered plants. It was hypothesized that the 10-20% contributions to transpiration resulting during dry soil periods came primarily from water stored in plant tissues. The authors concluded that the sensitivity of relative transpiration rates to changes in volumetric water content is approximately constant over a wide range of plant species.

The findings of Sinclair et al. 2005 also indicate that irrigating during droughts (or storing runoff and slowly releasing it to vegetated practices) should increase ET. Another means of maintaining adequate soil moisture to maximize ET is to design BMPs with internal water storage. A study by Hickman (2011) found that, due to greater available soil moisture, a bioretention cell with internal water storage (designed using a weighing lysimeter to assess ET) lost twice as much water to ET as a biofiltration cell without internal storage.

A multi-disciplinary group working in support of Minnesota’s stormwater manual update and Minimal Impact Design Standards (MIDS) researched the importance of tree evapotranspiration and canopy interception as related to stormwater management systems (Kestrel Design Group Team, 2013) offered several key implications for improving the recognition of the role of ET in tree-related or vegetated stormwater practices, quoted below (except where the Figure 2 reference is modified for Vermont’s conditions):

- ET is a large part of the hydrological cycle, even in urban areas, and design and crediting incentives for BMPs should aim to maximize ET.

- Directing more runoff to a BMP than just the amount of rain that falls on the BMP should increase the amount of ET in the BMP compared to ET of similar vegetation that received only the rain that falls on it. A very rough estimation from Figure 2 indicates that during mid-summer, vegetation should be able to evapotranspire 10-20% more rainfall than falls directly on the BMP. In the very coarse analysis presented here, the benefit of this practice appears to be limited relative to the same assessment completed in other areas of the country. A more detailed assessment is warranted to accurately quantify how much additional rainfall could be directed to and evapotranspired from BMPs in Vermont.
- Optimizing irrigation of vegetated practices, either by irrigating with runoff harvested from impervious surfaces or by building internal water storage into stormwater practices, should be encouraged to maximize ET during dry weather.

### 2.3. Infiltration

The growth of tree roots, as well as the decomposition of roots and leaf litter, increase soil infiltration rates and overall infiltration capacity. Numerous studies have quantified the impact of trees on infiltration rates (Herrera Environmental Consultants 2008). A study of infiltration before and after forest fires found that infiltration rates decreased by 20-30 percent (Wondzell 2003). A study completed in the North Carolina piedmont found that when the forest understory and leaf litter were removed from a mixed pine-hardwood forest, the resultant lawn had infiltration rates that were 65% lower compared to the forested condition (Kays 1980).

Conversely, field-scale studies of changes in stormwater runoff following the clear-cutting of forested basins in New Hampshire and Oregon showed increases in runoff of 23-32% for deciduous forest (Hornbeck et al. 1997, Martin and Hornbeck 2000) and 32% for coniferous forest (Jones 2000) in the clear-cut basins when compared to adjacent forested controls. On average, forests produce 30% to 50% less runoff than do grass lawn areas (Pitt et al. 1986), which in turn produce significantly less runoff than impervious surfaces.

Though trees have been shown to measurably increase the infiltration capacity of underlying soils in natural areas, this may not always be true in urbanized ones. Removal of leaves and organic buildup by homeowners, businesses, and municipal grounds crews is common and may degenerate the organic layer, and human and animal traffic may compact soils (Herrera Environmental Consultants 2008).

There is, however, a robust and rapidly evolving body of research regarding the ability of trees to provide infiltration benefits despite these limitations – and on ways to best engineer tree-planting areas in urban environments to both grow healthy trees and maximize the stormwater management benefits they provide. In one such study, black oak (*Quercus velutina* Lam.) and red maple (*Acer rubrum* L.) trees were installed in cylindrical planting sleeves surrounded by clay loam soil at two compaction levels (bulk density = 1.3 or 1.6 g cm<sup>-3</sup>) in irrigated containers. Roots of both species penetrated the more compacted soil, increasing infiltration rates by an average of 153% compared to an unplanted control (Bartens et al. 2008).

In addition to infiltrating runoff, soil stores rain water during and after a storm, making it available for plant growth. For example, one properly planted tree surrounded by suspended pavement, with 1000 cubic feet of uncompacted soil with 20% soil water storage capacity, can hold the 1 inch, 24 hour storm event from 2,400 square feet of impervious surface—an area much larger than just the area under the tree canopy (Shanstrom 2011). This example calculation, like most of those that are used to design bioretention systems with trees, accounts only for soil storage, not for interception or evapotranspiration.

### 2.4. Pollutant removal

Most recent research involving the pollutant removal efficiency of tree-related stormwater practices has focused primarily on tree-scale bioretention practices. Several recent literature reviews of lab and field studies of bioretention pollutant removal have concluded that bioretention systems, whether vegetated with trees or plants, are one of the most effective BMPs for pollutant removal (Shanstrom 2011a, Davis et al. 2012). Pollutant removal mechanisms include filtration, adsorption, and uptake and sequestration in plant material (Capiella et al. 2005, Davis et al. 2009). Over time, trees also increase the amount of organic matter in the soil, which binds many pollutants (Capiella et al. 2005).

High concentration and load reductions are consistently found for suspended solids, metals, polycyclic aromatic hydrocarbons (PAH), and other organic compounds (Denman 2006, Davis et al. 2009). The presence of vegetation also substantially improves retention of total nitrogen and total phosphorus; vegetated media is much more effective at removing dissolved phosphorus from solution and at reducing nitrate leaching from bioretention soil mixes or media (e.g., Henderson et al. 2007, Henderson 2009, Lucas and Greenway 2011, and the International BMP Database). Limited research suggests that bioretention can also effectively manage other pollutants, such as pathogenic bacteria and thermal pollution (Davis et al. 2009). Innovations in bioretention design to maximize nutrient removal, such as the “upturned elbow” to create an anerobic zone that facilitates denitrification (Brown et al. 2009, Davis et al. 2009), and the addition of media such as iron filings to bioretention mixes to improve phosphorus sorption (Erickson et al. 2012, Traver et al. 2013), also show great promise.



### 3. MAXIMIZING STORMWATER-RELATED BENEFITS AT THE TREE OR SITE SCALE

Consideration of soil and the overall site are critical to success, even (and perhaps especially) when the project seems as simple as planting a tree. Healthy trees require space, proper soil, drainage, and adequate water—and as the sites considered for tree planting become smaller and more urban, it becomes even more critical to keep these factors in mind (Capiella et al. 2006).

Total soil volume and the quality of the soil, including porosity (amount of available pore space), permeability (how interconnected pore spaces are), and infiltration rate (how quickly the water moves through the soil) are critical to the success of a tree (Sanders et al. 2013) and its ability to absorb stormwater (U.S. EPA 2013). These soil properties affect the amount of air, moisture, and nutrients that are available in the root zone and how much runoff is absorbed into the ground instead of flowing over the ground.

Big trees with large, dense canopies manage the most stormwater – and designing tree plantings to accommodate the largest size tree possible will increase their stormwater utility function (Figure 3).




Figure 3. Comparison of uncompact soil volume to projected mature tree size (trunk and canopy diameter), with estimates of stormwater storage per tree (Deep Root Partners 2011).

The effects of site-scale development, including the addition of impervious surfaces, along with the compaction of soils by heavy construction equipment, create challenges for both stormwater management and successful tree growth by reducing or preventing the infiltration of runoff into the ground (US EPA 2013). One way to address these problems, providing a solution for both, is to preserve existing trees and to generally minimize the disturbance of a site during development (Capiella et al. 2006). In urban areas and in many re-development situations, where historic land uses and compaction preclude the effective use of these strategies, tree planting areas can still be designed to increase infiltration and limit compaction, and can even be engineered to receive and process stormwater from streets, parking lots, and rooftops (Capiella et al. 2006, Casey Trees 2008, Day et al. 2012).

### 3.1. Soil Restoration and Tree Planting

Trees are a part of almost every urban and suburban development, yet mature urban trees are rare. There can be many reasons why these trees fail to grow to useful sizes, but the most critical is that they generally don't have access to sufficient amounts of soil, resulting in a short death and replacement cycle (Marritz 2012). Planting trees in conditions that will support long-term growth is one of the most important ways to ensure that trees can reliably function as green infrastructure. Simply planting “a million trees”, as envisioned in green infrastructure initiatives in cities like Los Angeles, New York, Salt Lake City and Philadelphia, isn't likely to result in long-term success for trees at development sites or in urban areas unless those trees are planted in ways that ensure their long-term success.

Healthy soils support vigorous tree and plant growth that intercepts rainfall, returning much of it to the sky through evaporation and transpiration. Healthy soil also provides additional important stormwater management functions including efficient water infiltration and storage, adsorption of excess nutrients, filtration of sediments, biological decomposition of pollutants, and moderation of peak stream flows and temperatures (Washington DOE 2012). In recognition of these benefits, several states have implemented soil restoration (including topsoil preservation, minimum compaction, compost or other soil amendment, deep tillage, and other strategies) as a required or optional stormwater management practice on development or redevelopment sites (see sidebar).

The nexus between soil restoration on development sites and the success of trees planted following typical development practices is an area of active and ongoing research. For example, since 2007, the Soil Rehabilitation Experiment Site (SRES) at Virginia Tech is being used to evaluate the effects of several soil improvement practices on soil physical properties and tree establishment (Day et al. 2012). Researchers are monitoring soil carbon sequestration, greenhouse gas emissions, soil infiltration and permeability, rooting depth, and a host of other factors to fully characterize the potential of these practices for restoring soils damaged by land development. Preliminary results demonstrate that “Soil Profile Rebuilding”—which includes a subsoiling procedure, addition of organic matter in the form of compost, replacement or addition of topsoil followed by tilling, and subsequent planting with woody plants—substantially improves tree establishment and growth during the first five years after planting when compared to typical land development practices (Day et al. 2012).

#### Soil Restoration Resources

Washington State's *Building Soil* guidebook for implementing soil quality and depth standards during development and redevelopment projects:

[http://www.soilsforsalmon.org/pdf/Soil\\_BMP\\_Manual.pdf](http://www.soilsforsalmon.org/pdf/Soil_BMP_Manual.pdf)

Virginia Tech's Soil Profile Rebuilding specification:

<http://urbanforestry.frec.vt.edu/SRES/specification.html>

Stone Environmental technical memo on soil restoration standards, and options for use as a stormwater BMP in Vermont:

[http://www.vtwaterquality.org/stormwater/docs/manualrevision/sw\\_Tech\\_Memo\\_Soil\\_Restoration.pdf](http://www.vtwaterquality.org/stormwater/docs/manualrevision/sw_Tech_Memo_Soil_Restoration.pdf)

### 3.2. Engineered Systems for Trees in Urban Settings

Techniques like minimal site disturbance, tree preservation, and soil preservation can all be reasonably planned for on larger lots, or in new development projects—but often these practices are simply not feasible in urban areas and smaller historic village centers. Impervious surfaces and compacted soils create major challenges,

preventing the infiltration of runoff into the ground. In these situations, un-compacted soil volumes sufficient for growing healthy trees to maturity can be provided by designing tree planting areas to increase infiltration and limit compaction even under pavement. In addition, tree planting area can also often be engineered to receive and process street and rooftop runoff. Several types of engineered systems that can support healthy trees in urban settings are briefly highlighted below.

### 3.2.1. Suspended pavement and structural cells

In a suspended pavement or structural cell system, pavement or the intended ground surface is supported by a network of pillars, piles, or structural cells (U.S. EPA 2013). The suspension system supports the weight and forces of the pavement above and allows the soil below to remain uncompacted over time, accommodating tree roots and both filtering and managing stormwater runoff under paved surfaces (Figure 3).

### 3.2.2. Structural soil

Structural soils are engineered soil mixes with a high porosity that allow tree roots to penetrate freely, and stormwater to infiltrate rapidly and then be stored until it percolates into the soil beneath (Day and Dickinson 2008). Tree root systems and the structural soil that supports them combine to form a shallow but extensive reservoir for capturing and storing stormwater.

Systems that include structural soils are designed to be used under asphalt or concrete pavements, or in tandem with pervious pavements, as the load-bearing and leveling layer. In addition to providing a compactable base for pavements, structural soil provides a soil component to the aggregate mix that facilitates root growth—common road bases do not have this tree-friendly component (U.S. EPA 2013). Two examples of structural soils that have been developed and tested in the United States are Cornell University’s CUSoil and Carolina Stalite (Day and Dickinson 2008).

### 3.2.3. Stormwater tree pits

A stormwater tree pit is similar to a traditional street tree pit design, but is modified so the pit accepts and treats storm water runoff and provides an improved planting environment for the tree (Capiella et al. 2006). When tree pits provide enough uncompacted soil volume to grow large-sized trees, they become an integral part of stormwater management (U.S. EPA 2013). While tree pits can be individual, connecting multiple tree pits by using soil paths or drains can increase soil volume for both trees and stormwater management opportunities (Casey Trees 2008, U.S. EPA 2013).

It is unusual, however, for ultra-urban areas to have enough space to provide adequate uncompacted soil volume to grow truly large, healthy trees in a stormwater tree pit. To grow a tree with a canopy diameter of 30 feet, for example, would require roughly 1,413 cubic feet of soil, assuming two cubic feet of soil per square foot of canopy (see Figure 3). Assuming a three-foot soil depth, the needed surface area is 471 square feet (15.7 by 30 feet, or 10 by 47 feet). Very few already-constructed urban streets have this much open space.



*Figure 4. A structural cell system under construction on Cherry Street in Burlington, VT.*

### 3.2.4. Forested bioretention and bioinfiltration

Bioretention and bioinfiltration facilities are shallow, landscaped depressions that contain a layer of prepared soil, a mulch layer, and vegetation. These facilities provide filtering of storm water runoff by temporarily ponding water during storms. Bioretention facilities have underdrain systems, while bioinfiltration facilities allow runoff to infiltrate into existing site soils (infiltration rates greater than 0.5 inches per hour) (Capiella et al. 2006). The concept design for a forested bioretention system is intended not only to incorporate trees and shrubs, but to improve growing conditions for trees and decrease potential engineering conflicts (Capiella et al. 2006). The small footprint of these facilities (generally 5% of the impervious area they receive drainage from) means that they may be used in many applications.

### 3.3. Tree Selection, Siting, and Planting

The urban landscape represents an especially harsh environment for trees, complete with a variety of pollutants, temperature extremes, hydrologic modifications, compacted soils, invasive plants, and many other factors that make it difficult to sustain healthy trees. Part 3 of the Urban Watershed Forestry Manual (2006) presents several well-tested design principles for successful urban tree planting, adapted from Urban (1999) and GFC (2001):

- 1. Provide adequate soil volume to support trees at maturity. A general guideline is to provide at least two cubic feet of usable soil for every one square foot of mature canopy (the area within the projected mature dripline of the tree). Soil volumes of planting areas should be designed to be interconnected so trees can share rooting space.*
- 2. Preserve and improve soil quality. Limit clearing and grading to protect native soils at the site. Soil volume should be accessible to air, water, and nutrients. This is best done by separating paving from tree's rooting area, which also allows for periodic inspection of the planting area. Soils should be amended where needed to improve drainage and fertility.*
- 3. Provide adequate space for tree to grow. Design surrounding infrastructure to accommodate long-term growth of tree, and space trees appropriately to allow for long-term growth and management.*
- 4. Select trees for diversity and site suitability. Plant a variety of species that are tolerant of the climate and soil conditions as well as any urban impacts at the site.*
- 5. Protect trees from other impacts. Develop designs that protect the tree over its entire life from pedestrian traffic, toxic runoff, browsing, high temperatures, and other urban impacts.*

#### More on Engineered Systems for Trees

*Urban Watershed Forestry Manual, Part 2: Conserving and Planting Trees at Development Sites:*

<http://www.treesearch.fs.fed.us/pubs/19936>

*Tree Space Design: Growing the Tree out of the Box:* <http://caseytrees.org/wp-content/uploads/2012/02/tree-space-design-report-2008-tsd.pdf>

*Stormwater to Street Trees: Engineering Urban Forests for Stormwater Management:*

<http://water.epa.gov/polwaste/green/upload/stormwater2streettrees.pdf>

*Managing Stormwater for Urban Sustainability Using Trees and Structural Soils:*

<http://www.vtfpr.org/urban/documents/TreesAndStructuralSoilsManual.pdf>

A robust variety of resources are widely available to support proper site selection, decision making about which tree species to plant, site preparation and tree planting, and tree establishment and ongoing maintenance (see sidebar below).

### **Tree Selection, Siting, and Planting Resources**

Vermont Urban and Community Forestry Program’s Community Forestry Library Tree Planting

References: [http://www.vtfpr.org/urban/for\\_urbcomm\\_library.cfm#Planting](http://www.vtfpr.org/urban/for_urbcomm_library.cfm#Planting)

Vermont Urban and Community Forestry Program’s Tree Selection Tool:

<http://www.vtfpr.org/urban/treeselectiontool.cfm>

Center for Watershed Protection and US Forestry Service’s *Urban Watershed Forestry Manual, Part 3: Urban Tree Planting Guide*:

[http://www.na.fs.fed.us/pubs/uf/watershed3/urban\\_watershed\\_forestry\\_manual\\_part3.pdf](http://www.na.fs.fed.us/pubs/uf/watershed3/urban_watershed_forestry_manual_part3.pdf)

---

## 4. REFERENCES

- Akbari, H.; Davis, S.; Dorsano, S.; Huang, J.; Winnett, S., eds. 1992. Cooling our communities – a guidebook on tree planting and light-colored surfacing. U.S. Environmental Protection Agency. Washington, DC. Accessed at <http://escholarship.org/uc/item/98z8p10x> on November 13, 2013.
- Bartens, Julia, Susan D. Day, J. Roger Harris, Joseph E. Dove, and Theresa M. Wynn. 2008. Can Urban Tree Roots Improve Infiltration through Compacted Subsoils for Stormwater Management? *J. Environ. Qual.* 37:2048–2057. Accessed at <http://www.urbanforestryinstitute.com/uploads/volume/Can%20Urban%20Tree%20Roots%20Improve%20Infiltration%20through%20Compacted%20Subsoils%20for%20Stormwater%20Management.pdf> on May 23, 2013.
- Bartens, Julia, Susan D. Day, J. Roger Harris, Theresa M. Wynn, and Joseph E. Dove. 2009. Transpiration and Root Development of Urban Trees in Structural Soil Stormwater Reservoirs. *Environmental Management* 44:646–657. Accessed at <http://www.urbanforestryinstitute.com/uploads/volume/Transpiration%20and%20Root%20Development%20of%20Urban%20Trees%20in%20Structural%20Soil%20Stormwater%20Reservoirs.pdf> on May 23, 2013.
- Brown, Robert, William F. Hunt, and Shawn G. Kennedy. 2009. Designing Bioretention with an Internal Water Storage (IWS) Layer. North Carolina State University Cooperative Extension paper AG-588-19W. Accessed at <http://www.bae.ncsu.edu/stormwater/PublicationFiles/IWS.BRC.2009.pdf> on December 19, 2013.
- Cappiella, Karen, Tom Schueler, and Tiffany Wright. 2005. Urban Watershed Forestry Manual, Part 1: Methods for Increasing Forest Cover in a Watershed. Report no. NA-TP-04-05, prepared by the Center for Watershed Protection for the USDA Forest Service, Northeastern Area, July 2005. Accessed at <http://www.treesearch.fs.fed.us/pubs/19916> on November 13, 2013.
- Cappiella, Karen, Tom Schueler, and Tiffany Wright. 2006. Urban Watershed Forestry Manual Part 2: Conserving and Planting Trees at Development Sites. Report no. NA-TP-01-06, prepared by the Center for Watershed Protection for the USDA Forest Service, Northeastern Area, May 2006. Accessed at <http://www.treesearch.fs.fed.us/pubs/19936> on November 13, 2013.
- Cappiella, Karen, Tom Schueler, and Tiffany Wright. 2006. Urban Watershed Forestry Manual, Part 3: Urban Tree Planting Guide. Prepared by the Center for Watershed Protection for the USDA Forest Service, Northeastern Area, March 2006. Accessed at [http://www.na.fs.fed.us/pubs/uf/watershed3/urban\\_watershed\\_forestry\\_manual\\_part3.pdf](http://www.na.fs.fed.us/pubs/uf/watershed3/urban_watershed_forestry_manual_part3.pdf) on November 13, 2013.
- Casey Trees. 2008. Tree Space Design: Growing the Tree Out of the Box. Accessed at <http://caseytrees.org/wp-content/uploads/2012/02/tree-space-design-report-2008-tds.pdf> on April 2, 2013.
- Center for Watershed Protection and US Forest Service - Northeastern Area. 2008. Watershed Forestry Resource Guide: Using Trees to Reduce Stormwater Runoff. Web page updated 2008. Accessed at <http://www.forestsforwatersheds.org/reduce-stormwater/> on April 23, 2013.
- Davis, A.P., Hunt, W.F., Traver, R.G., and Clar, M. 2009. Bioretention Technology: An Overview of Current Practice and Future Needs. *J. Environ. Eng. ASCE*. 135(3) 109-117. Accessed at [http://dx.doi.org/10.1061/\(ASCE\)0733-9372\(2009\)135:3\(109\)](http://dx.doi.org/10.1061/(ASCE)0733-9372(2009)135:3(109)) (subscription required) on May 23, 2013.
- Davis, A.P., Traver, R.G., Hunt, W.F., Brown, R.A., Lee, R. and Olszewski, J.M.. 2012. Hydrologic Performance of Bioretention Stormwater Control Measures. *J. Hydrologic Eng, ASCE* 17(5), 604-614.

Accessed at [http://dx.doi.org/10.1061/\(ASCE\)HE.1943-5584.0000467](http://dx.doi.org/10.1061/(ASCE)HE.1943-5584.0000467) (subscription required) on May 23, 2013.

Day, Susan, et al. 2009. Stormwater Management: Using trees and structural soils to improve water quality. Web site last updated 2009. Accessed at <http://urbanforestry.frec.vt.edu/stormwater/> on May 28, 2013.

Day, Susan, et al. 2012. Soil Rehabilitation Experiment Site: A long-term study of urban soil rehabilitation for enhanced tree growth. Web site last updated 2012. Accessed at <http://urbanforestry.frec.vt.edu/SRES/Index.html> on May 28, 2013.

Deep Root Partners, LLP. 2011. How Much Soil to Grow a Big Tree? Fact sheet dated January 2011. Accessed at [http://www.deeproot.com/silvapdfs/resources/supporting/How\\_Much\\_Soil\\_To\\_Grow\\_A\\_Big\\_Tree.pdf](http://www.deeproot.com/silvapdfs/resources/supporting/How_Much_Soil_To_Grow_A_Big_Tree.pdf) on December 19, 2013.

Denman, Liz. 2006. Are Street Trees And Their Soils An Effective Stormwater Treatment Measure? Paper presented at the 7th National Street Tree Symposium. Accessed at [http://contextsensitivesolutions.org/content/reading/are\\_street\\_trees\\_and\\_their\\_soil\\_/resources/STREETTREE\\_S\\_LizDenman.pdf](http://contextsensitivesolutions.org/content/reading/are_street_trees_and_their_soil_/resources/STREETTREE_S_LizDenman.pdf) on December 18, 2013.

Envirocast. 2003. Seeing the forests through the trees: Part 2, autumn leaf fall and the watershed. *Envirocast* 12(2); 1-4.

Erickson, A.J., J.S. Gulliver and P.T. Weiss. 2012. Capturing Dissolved Phosphorus with Iron Enhanced Sand Filtration. *Water Research* 46(9): 3032–3042. Accessed at <http://www.sciencedirect.com/science/article/pii/S0043135412001728> on December 19, 2013.

Geiger, J.R. 2001. Fact Sheet #1: Benefits of the urban forest. Davis, CA: USDA Forest Service, Pacific Southwest Research Station. Accessed at [http://www.fs.fed.us/psw/programs/uesd/uep/products/cufr\\_179\\_UFfactsheet1.pdf](http://www.fs.fed.us/psw/programs/uesd/uep/products/cufr_179_UFfactsheet1.pdf) on November 13, 2013.

Grimmond, C.S.B., and T.R. Oke. 1999. Rates of evaporation in urban areas. Impacts of Urban Growth on Surface and Ground Waters. International Association of Hydrological Sciences Publication, 259, 235-243. Accessed at <http://www.kcl.ac.uk/ip/suegrimmond/publishedpapers/GrimmondOkeIAHS1999.pdf> on March 4, 2014.

Henderson, C., Greenway, M., Phillips, I. 2007. Removal of dissolved nitrogen, phosphorus and carbon from stormwater by biofiltration mesocosms. *Water Science Technology* 55(4), 183-191. Accessed at <http://www.iwaponline.com/wst/05504/wst055040183.htm> (subscription required) on May 23, 2013.

Henderson, C.F.K. 2009. The Chemical and Biological Mechanisms of Nutrient Removal from Stormwater in Bioretention Systems. Thesis. Griffith School of Engineering, Griffith University.

Herrera Environmental Consultants. 2008. The Effects of Trees on Stormwater Runoff. Report prepared for Seattle Public Utilities, February 14, 2008. Accessed at [http://www.psparchives.com/publications/our\\_work/stormwater/lid/clearing\\_grading/Effect%20of%20Trees%20on%20Stormwater%20Lit%20Review-Herrera.pdf](http://www.psparchives.com/publications/our_work/stormwater/lid/clearing_grading/Effect%20of%20Trees%20on%20Stormwater%20Lit%20Review-Herrera.pdf) on April 25, 2013.

Hickman, J.M. Jr. 2011. Evaluation the Role of Evapotranspiration in the Hydrology of Bioinfiltration and bioretention Basins using Weighing Lysimeters. M.S. thesis, Villanova University. Accessed at <https://library.villanova.edu/Find/Record/1335594/Details> on March 5, 2014.

Hornbeck, J.W., C.W. Martin, and C. Eagar. 1997. Summary of Water Yield Experiments at Hubbard Brook Experimental Forest, New Hampshire. *Canadian Journal of Forest Research-Revue Canadienne De Recherche*

- Forestiere* 27(12): 2043-2052. Accessed at <http://www.nrcresearchpress.com/doi/abs/10.1139/x97-173#.UrGIBCD0nag> on December 18, 2013.
- Jones, J.A. 2000. Hydrologic Processes and Peak Discharge Response to Forest Removal, Regrowth, and Roads in 10 Small Experimental Basins, Western Cascades, Oregon. *Water Resources Research* 36(9): 2621-2642. Accessed at <http://andrewsforest.oregonstate.edu/pubs/pdf/pub2567.pdf> on December 18, 2013.
- Kays, Barrett L. 1980. Relationship of forest destruction and soil disturbance to increased flooding in suburban North Carolina piedmont. In *METRIA—Proceedings of the Third Conference of the Metropolitan Tree Improvement Alliance*, Rutgers State University, NJ; p. 118-125. Accessed at <http://www.ces.ncsu.edu/fletcher/programs/nursery/metria/metria03/m312.pdf> on November 13, 2013.
- Kestrel Design Group Team (The Kestrel Design Group Inc, with Dr. William Hunt, PE and Ryan Winston, PE - North Carolina State University, Greg McPherson - USDA Forest Service, Qingfu Xiao – University of California, Davis, Joe Purohit - Ecolayers). 2013. *The Roles and Effects of Tree Evapotranspiration and Canopy Interception in Stormwater Management Systems and Strategies: A Review of Current Literature and Proposed Methodology For Quantification In The MIDS Calculator Application Objective 1, Task 13*. Prepared for: Minnesota Pollution Control Agency (MPCA). Accessed at [http://stormwater.pca.state.mn.us/images/a/ab/Trees\\_Task\\_13\\_ET\\_interception\\_credits.docx](http://stormwater.pca.state.mn.us/images/a/ab/Trees_Task_13_ET_interception_credits.docx) on March 5, 2014.
- Lucas, W. C.; Greenway, M. 2008. Nutrient Retention in Vegetated and Non-vegetated Bioretention Mesocosms. *J. Irrig. Drain. E-ASCE* 134 (5): 613-623. Accessed at [http://dx.doi.org/10.1061/\(ASCE\)0733-9437\(2008\)134:5\(613\)](http://dx.doi.org/10.1061/(ASCE)0733-9437(2008)134:5(613)) on May 23, 2013.
- Lucas, W.C., and M. Greenway. 2011. Hydraulic response and nitrogen retention in bioretention mesocosms with regulated outlets: part II – nitrogen retention. *Water Environment Research*, 83(8): 703-713. Accessed at <http://dx.doi.org/10.2175/106143011X12989211840936> on May 23, 2013.
- Marritz, Leda. 2012. A Million Trees? Only If We Can Keep Them Around. Article dated April 18, 2012. Accessed at <http://nextcity.org/daily/entry/a-million-trees-only-if-we-can-keep-them-around> on January 7, 2014.
- Martin, C.W., J.W. Hornbeck, G. E. Likens, and D. C. Buso. 2000. Impacts of Intensive Harvesting on Hydrology and Nutrient Dynamics of Northern Hardwood Forests. *Canadian Journal of Fisheries and Aquatic Sciences* 57(Suppl. 2): 19–29.
- Metro, 2002. Trees for green streets: an illustrated guide. Portland, OR. Accessed at <http://www.oregonmetro.gov/index.cfm/go/by.web/id=26337> on November 13, 2013.
- Metro Water Services (Nashville, Tennessee). 2012. Metropolitan Nashville – Davidson County Stormwater Management Manual Volume 5: Low Impact Development Stormwater Management Manual. Effective June 2012. Accessed at [https://www.nashville.gov/portals/0/SiteContent/WaterServices/Stormwater/docs/SWMM/vol5/SWMM\\_Vol5\\_LIDManual\\_2012.pdf](https://www.nashville.gov/portals/0/SiteContent/WaterServices/Stormwater/docs/SWMM/vol5/SWMM_Vol5_LIDManual_2012.pdf) on November 5, 2013.
- Midwest Urban Tree Canopy Project. 2011. The Value of Urban Trees: Stormwater Management. Web page last updated 2011. Accessed at <http://midwestutc.org/stormwater.aspx> on April 24, 2013.
- Minnesota Pollution Control Authority. 2013. Minnesota Stormwater Manual – Trees Overview page. Page last modified October 31, 2013 Accessed at <http://stormwater.pca.state.mn.us/index.php/Trees> on November 6, 2013.



- Northeast Regional Climate Center and National Climate Data Center. 2014. Monthly climate data summary tables, Burlington International Airport, Station ID USW00014742, January 1974-December 2004. Accessed at [http://www.nrcc.cornell.edu/menu\\_station.html](http://www.nrcc.cornell.edu/menu_station.html) on March 5, 2014.
- Pennsylvania Department of Environmental Protection, Bureau of Watershed Management. 2008. Pennsylvania Stormwater Best Management Practices Manual. Revised December 30, 2008. Accessed at <http://www.elibrary.dep.state.pa.us/dsweb/View/Collection-8305> on August 13, 2012.
- Pitt, D. G.; Gould, W. G.; LaSota, L. 1986. Landscape design to reduce surface water pollution in residential areas. Water Resources Information Bulletin No. 5. College Park, MD: University of Maryland Cooperative Extension. Accessed at [http://bre.umd.edu/WR\\_Files/WR32.PDF](http://bre.umd.edu/WR_Files/WR32.PDF) on November 13, 2013.
- Prince Georges County, MD. 2012. Urban Tree Canopy Fact Sheet and Planting Guidance. Accessed at <http://www.princegeorgescountymd.gov/sites/StormwaterManagement/CleanWaterActFees/BMP/TreeCanopy/Pages/default.aspx> on November 12, 2013.
- Sanders, Jessica, Jason Grabosky, and Paul Cowie. 2013. Establishing Maximum Size Expectations for Urban Trees with Regard to Designed Space. *Arboriculture & Urban Forestry Online* 39(2). Accessed at <http://joa.isa-arbor.com/articles.asp?JournalID=1&VolumeID=39&IssueID=2> on April 16, 2013.
- Shanstrom, Nathalie. 2011. Stormwater Quantity and Rate Control Benefits of Trees in Uncompacted Soil. Posted on July 20, 2011. Accessed at <http://www.deeproot.com/blog/blog-entries/stormwater-quantity-and-rate-control-benefits-of-trees-in-uncompacted-soil> on May 28, 2013.
- Shanstrom, Nathalie. 2011a. Stormwater Quality Benefits of Bioretention with Trees. Posted on August 1, 2011. Accessed at <http://www.deeproot.com/blog/blog-entries/stormwater-quality-benefits-of-bioretention-with-trees> on April 25, 2013.
- Shanstrom, Nathalie. 2012. Bioretention and Nutrient Removal, Part 3: What factors affect vegetation performance? Posted on September 10, 2012. Accessed at <http://www.deeproot.com/blog/blog-entries/bioretention-and-nutrient-removal-part-3-what-factors-affect-vegetation-performance> on May 23, 2013.
- Sinclair, Thomas R., Michelle Holbrook, and Maciej A. Zwieniecki. 2005. Daily transpiration rates of woody species on drying soil. *Tree Physiology* 25, 1469–1472. Accessed at [http://research.eescience.utoledo.edu/lees/papers\\_pdf/Sinclair\\_2005\\_TreePhys.pdf](http://research.eescience.utoledo.edu/lees/papers_pdf/Sinclair_2005_TreePhys.pdf) on March 5, 2014.
- Traver, Robert, Allen Davis, William Hunt, and John Gulliver. 2013. LID Research Panel. International Low Impact Development Symposium, St. Paul, Minnesota, August 18-21, 2013. Abstract accessed at <http://www.cce.umn.edu/Documents/CPE-Conferences/LIDS/LIDS-Final-Program-Book.pdf> on December 19, 2013.
- Urban, James. 2008. Up By Roots: Healthy Soils and Trees in the Built Environment. Illinois: International Society of Arboriculture, 2008. Ordering information at <http://www.amazon.com/Up-By-Roots-James-Urban/dp/B001F93W64>
- U.S. Environmental Protection Agency. 2013. Stormwater to Street Trees: Engineering Urban Forests for Stormwater Management. Document number EPA 841 B 13 001, January 2013. Accessed at <http://water.epa.gov/polwaste/green/upload/stormwater2streettrees.pdf> on November 12, 2013.
- Vermont Urban and Community Forestry Program. 2013. Guide to Tree Ordinances for Vermont Communities. Vermont Department of Forests, Parks and Recreation in partnership with the University of

- Vermont Extension, January 2013. Accessed at <http://www.vtinvasives.org/sites/default/files/treeordinanceguide.pdf> on October 22, 2013.
- Washington Department of Ecology. 2012. Stormwater Management Manual for Western Washington. Publication Number 12-10-030, Effective August 1, 2012. Accessed at <https://fortress.wa.gov/ecy/publications/publications/1210030.pdf> on August 22, 2012.
- Wondzell, S.M., and J.G. King. 2003. Postfire Erosional Processes in the Pacific Northwest and Rocky Mountain Regions. *Forest Ecology and Management* 178(1-2):75-87. Accessed at <http://www.fs.fed.us/rm/boise/research/fisheries/fire/FAE%20Papers/FE&M%20Formatted%20version%20Wondzell&King.pdf> on December 18, 2013.
- Xiao, Q.; McPherson, E. G.; Ustin, S. L.; Grismer, M. E.; Simpson, J. R. 2000. Winter rainfall interception by two mature open-grown trees in Davis, CA. *Hydrological Processes* 14: 763-784. Accessed at [http://www.itreetools.org/streets/resources/Winter\\_rainfall\\_interception\\_Xiao.pdf](http://www.itreetools.org/streets/resources/Winter_rainfall_interception_Xiao.pdf) on November 13, 2013.
- Xiao, Q; E.G. McPherson. 2002. Rainfall Interception by Santa Monica's Municipal Urban Forest. *Urban Ecosystems* 6:291-302. Accessed at <http://link.springer.com/article/10.1023%2FB%3AUECO.0000004828.05143.67#page-1> on March 5, 2014.